


MAGNETIC DRILLING MACHINE

MODEL: MAGTAP30 (MT30)




Core drilling




Ø 12 - 100 mm

Twist drilling




Ø 3 - 32 mm

Countersinking




Ø 10 - 55 mm

Tapping



Ø 6 - 30 mm

Thanks to "HEAVY-DUTY" Twin Rail Slide System easily 240 mm cutting depth possible.



** All machines supplied in plastic carry case with allen keys / safety chain with carabina hook / coolant system and drill drift MT 3 all models available in 110/120 Volts 50/60Hz and 220/240 Volts AC 50/60Hz

Magtap 30 switch panel with fullwave electronic speed control with constant torque also forward and reverse with built in time delay for motor start giving motor and gearbox protection when switching from forward operation to reverse operation when tapping or reaming.



Right/left running



Full wave electronic



Thermal/overheat protection



Gear stages
Speed full load

① = 60 - 140 min⁻¹

② = 200 - 470 min⁻¹



MODEL: MAGTAP30 (MT30)

CUTTER CAPACITY	12 - 100 mm
DRILLING CAPACITY	3 - 32 mm
TAPPING CAPACITY	6 - 30 mm
COUNTERSINK CAPACITY	10 - 55 mm
REAMING CAPACITY	6 - 30 mm
MOTOR WATTS	1800 W
TOTAL POWER WATTS	1860 W
SPEED LOW GEAR RPM	60 - 140 RPM
SPEED HIGH GEAR RPM	200 - 470 RPM
MECHANICAL CLUTCH	YES
ARBOR/DRIVE	MT3
SLIDE STROKE	255 mm
MAGNETIC ADHESION	2050 kg
MAGNETIC FOOT	102x212 mm
MAGNET	FIXTED
OVERALL HEIGHT	480 mm
OVERALL WIDTH	130 mm
OVERALL LENGTH	340 mm
ARBOR FOR CUTTERS	19 mm WELDON
COOLANT SYSTEM	THROUGH ARBOR
WEIGHT	23 kg

* 12 months comprehensive warranty as standard.

Magbroach (UK) Ltd

Agent: